



## Manual Cold Saw

With 275 mm (11") Blade

### CS-275M

- Miters 60 degrees right and 90 left
- Centering vise
- Stop mechanism
- Heavy cast construction
- Cuts ferrous and non-ferrous metals
- 75 mm (3") capacity
- 400V, 3-phase, 50Hz



## Manual Cold Saw

With 350 mm (14") Blade

### CS-350M

- Miters 60 degrees left and 90 right
- Centering vise
- Stop mechanism
- Heavy cast construction
- Cuts ferrous and non-ferrous metals
- 115 mm (4½") capacity
- 400V, 3-phase, 50Hz



## Semi-Automatic Cold Saw With 275 mm (11") Blade

### CS-275SA

Pneumatic centering vise,  
hydraulic feed

Automatic shut-off and vise release

Miters 60 degrees right and 90 left

Stop mechanism

Heavy cast construction

Cuts ferrous and non-ferrous metals

75 mm (3") capacity

400V, 3-phase, 50Hz



## Semi-Automatic Cold Saw With 350 mm (14") Blade

### CS-350SA

Pneumatic centering vise,  
hydraulic feed

Automatic shut-off and vise release

Miters left or right,  
60 degrees left and 90 right

Stop mechanism

Heavy cast construction

Cuts ferrous and non-ferrous metals

115 mm (4½") capacity

400V, 3-phase, 50Hz



# Cold Saw Capacities

	CS-275M				CS-275SA			
	Imperial		Metric		Imperial		Metric	
Max Blade Size	11"		275 mm		11"		275 mm	
Blade RPM (Non-Ferrous)	120		120		120		120 rpm	
Blade RPM (Ferrous)	60		60		60		60	
Head Swivel (Degrees)	90/0/45		90/0/45		90/0/45		90/0/45	
Electrical Requirements	400V, 3-phase, 50Hz		400V, 3-phase, 50Hz		400V, 3-phase, 50Hz		400V, 3-phase, 50Hz	
HP	3		3 (2.25 Kw)		3		3 (2.25 Kw)	
Clamping	Manual		Manual		Pneumatic		Pneumatic	
Cold Saw Type	Manual		Manual		Semi-Automatic		Semi-Automatic	
Length	36"		915 mm		36"		915 mm	
Width	30"		762 mm		30"		762 mm	
Height	59"		1499 mm		59"		1499 mm	
Weight	528 lbs.		240 kg		600 lbs.		272 kg	
<b>Profiles</b>								
Degrees	90	45	90	45	90	45	90	45
Sold Round	0	0	0	0	0	0	0	0
Round Tube	3"	2.5"	76 mm	63.5 mm	3"	2.5"	76 mm	63.5 mm
L-Shape	3" x 3"	2.25" x 2.25"	76 mm x 76 mm	57 mm x 57 mm	3" x 3"	2.25" x 2.25"	76 mm x 76 mm	57 mm x 57 mm
Square Tube	3"	2.5"	76 mm	63.5 mm	3"	2.5"	76 mm	63.5 mm
Rectangle	2.75" x 3"	2.5" x 2.25"	76 mm x 70 mm	63.5 mm x 57 mm	2.75" x 3"	2.5" x 2.25"	76 mm x 70 mm	63.5 mm x 57 mm

	CS-350M				CS-350SA			
	Imperial		Metric		Imperial		Metric	
Max Blade Size	14"		350 mm		14"		356 mm	
Blade RPM (Non-Ferrous)	52		52		52		52	
Blade RPM (Ferrous)	26		26		26		26	
Head Swivel (Degrees)	45/0/90		45/0/90		45/0/90		45/0/90	
Electrical Requirements	400V, 3-phase, 50Hz		400V, 3-phase, 50Hz		400V, 3-phase, 50Hz		400V, 3-phase, 50Hz	
HP	4		4 (3 Kw)		4		4 (3 Kw)	
Clamping	Manual		Manual		Pneumatic		Pneumatic	
Cold Saw Type	Manual		Manual		Semi-Automatic		Semi-Automatic	
Length	30"		762 mm		30"		762 mm	
Width	42"		1067 mm		42"		1067 mm	
Height	60"		60 mm		60"		60 mm	
Weight	748 lbs.		340 kg		880 lbs.		399 kg	
<b>Profiles</b>								
Degrees	90	45	90	45	90	45	90	45
Sold Round	2.5"	1.5"	63.5 mm	38 mm	2.5"	1.5"	63.5 mm	38 mm
Round Tube	4.5"	3"	114 mm	76 mm	4.5"	3"	114 mm	76 mm
L-Shape	4.5" x 4.5"	3" x 3"	114 mm x 114 mm	76 mm x 76 mm	4.5" x 4.5"	3" x 3"	114 mm x 114 mm	76 mm x 76 mm
Square Tube	4.5"	3"	114 mm	76 mm	4.5"	3"	114 mm	76 mm
Rectangle	4.5" x 3.5"	3" x 2.5"	114 mm x 89 mm	76 mm x 63.5 mm	4.5" x 3.5"	3" x 2.5"	114 mm x 89 mm	76 mm x 63.5 mm

Changes to specifications may occur without notice.