

Horizontal Band Saw

172 mm (6³/₄") Capacity

BS-210M

- Cuts metal and more
- 19 mm (¾") blade standard
- Hydraulic and manual feed
- Variable speed DC motor
- Single mitering
- Quick vise feature
- Direct drive
- 220V, single-phase, 50Hz



Horizontal Band Saw

230 mm (9") Capacity

BS-250M

Cuts metal and more

25 mm (1") blade standard

Hydraulic and manual feed

Variable speed DC motor

Single mitering

Quick vise feature

Direct drive

220V, single-phase, 50Hz



Horizontal Band Saw

268 mm (10½") Capacity

BS-350M



Cuts metal and more
25 mm (1") blade standard

Hydraulic and manual feed

Variable speed DC motor

Automatic shut-off / broken blade feature

Dual mitering

Quick vise feature

Direct drive

220V, single-phase, 50Hz



Band Saw Capacities

	BS-210M						BS-250M					
	Imperial			Metric			Imperial			Metric		
Blade Size	0.75"			19 mm			1"			25 mm		
Variable Blade Speed	115' to 279' per minute			35 m to 86 m per minute			115' to 279' per minute			35 m to 85 m per minute		
HP	1.5			1.5 (1.12 Kw)			2			2 (1.5 Kw)		
Broken Blade Tensioning Device	Yes			Yes			Yes			Yes		
Manual / Controlled Descent	Both			Both			Both			Both		
Power Requirements	220V, single-phase, 50Hz			220V, single-phase, 50Hz			220V, single-phase, 50Hz			220V, single-phase, 50Hz		
Mitering Feature	Single			Single			Single			Single		
Length	45.5"			1166 mm			61"			1550 mm		
Width	22.5"			574 mm			29"			737 mm		
Height	32.5"			828 mm			36"			914 mm		
Weight	344 lbs.			156 kg			475 lbs.			216 kg		
Cutting Profiles												
Degrees	90	45	60	90	45	60	90	45	60	90	45	60
Round	6.75"	4.75"	2.75"	172 mm	121 mm	70 mm	9"	6"	3.5"	229 mm	152 mm	89 mm
Square	6.75"			172 mm			8.5"	5.875"	3.375"	216 mm	149 mm	86 mm
Rectangle	8.25" x 6.75" at 90 Degrees			210 mm x 172 mm at 90 degrees			8" x 9.5" at 90 Degrees			203 mm x 241 mm at 90 Degrees		

	BS-350M							
	Imperial				Metric			
Blade Size	1"				25 mm			
Variable Blade Speed	66' to 279' per minute				20 m to 85 m per minute			
HP	2				2 (1.5 Kw)			
Broken Blade Tensioning Device	Yes				Yes			
Manual / Controlled Descent	Both				Both			
Power Requirements	220V, single-phase, 50Hz				220V, single-phase, 50Hz			
Mitering Feature	Dual				Dual			
Length	74"				1880 mm			
Width	30"				762 mm			
Height	44"				1118 mm			
Weight	800 lbs.				363 kg			
Cutting Profiles								
Degrees	90	45	60	45L	90	45	60	45L
Round	10.5"	9.5"	6.25"	8"	267 mm	241 mm	203 mm	159 mm
Square	10.25"	8.5"	6"	7.25"	260 mm	216 mm	184 mm	152 mm
Rectangle	8.5" x 13.5" at 90 Degrees				216 mm x 343 mm at 90 Degrees			

Changes to specifications may occur without notice.