



# Tube & Pipe Notcher

Eccentric Cut

## TN-800

No tooling changes  
up to 76 mm (3") OD

Perfect weld joint

13 mm (1/2") min. /  
76 mm (3") max. capacity

Angles and offsets

Fast and clean

220V, single-phase, 50Hz

Patent No: 6,435,783



Set to desired OD. Turn hand wheel counter clockwise. One revolution per weld joint.

# Tube & Pipe Notcher

Abrasive Style With Grinder

## TN-900

19 mm to 76 mm ( $\frac{3}{4}$ " - 3") capacity

Can use 102 mm to 152 mm  
(4" - 6") wide belts

Belts are non-proprietary

Easy lever feed with stop

Angles and offsets

Reversible motor and rear grinding station

220V, single-phase, 50Hz, 5HP motor



Centering vise



Grinding station



## Rotary Draw Bender Capacities

	RDB-100-S		RDB-150-AS		RDB-300-S	
	Imperial	Metric	Imperial	Metric	Imperial	Metric
Mild Steel Pipe (Schedule 40)	1"	33 mm (3 mm)	2"	60 mm (4 mm)	2"	60 mm (4 mm)
Aluminum Pipe (Schedule 40)	1"	33 mm (3 mm)	2"	60 mm (4 mm)	2.5"	73 mm (5 mm)
Stainless Steel Pipe (Schedule 40)	.75"	27 mm (4 mm)	1.5"	48 mm (3.7 mm)	1.5"	48 mm (3.7 mm)
Mild Steel Round Tube (Wall)	1.75" (.083")	45 mm (2 mm)	2.5" (.125")	64 mm (3 mm)	3" (.095")	76 mm (2.5 mm)
Aluminum Round Tube (Wall)	2" (.125")	50 mm (3 mm)	2.5" (.156")	64 mm (4 mm)	2.5" (.156")	64 mm (4 mm)
Stainless Steel Round Tube (Wall)	1.5" (.083")	38 mm (2 mm)	2.375" (.125")	60 mm (3 mm)	2.375" (.154")	60 mm (4 mm)
Chromolly Round Tube (Wall)	1.5" (.083")	38 mm (2 mm)	2" (.125")	51 mm (3 mm)	2" (.125")	51 mm (3 mm)
Mild Steel Solid Rod	1"	25 mm	1.25"	32 mm	1.25"	32 mm
Mild Steel Box Section (Wall)	1" (.125")	25 mm (3 mm)	2" (.125")	51 mm (3 mm)	2" (.125")	51 mm (3 mm)
Minimum Outside Diameter (OD)	0.25"	6.5 mm	0.25"	6.5 mm	0.25"	6.5 mm
Maximum Center Line Radius	7"	178 mm	7" / 8"	178 mm / 203 mm	15"	381 mm
Minimum CLR	0.5"	13 mm	0.5"	13 mm	0.5"	13 mm
Power Requirements	N/A		220V, single-phase, 50Hz		220V, single-phase, 50Hz	
Weight	390 Lbs.	176 kg	640 Lbs.	290 kg	710 Lbs.	322 kg
Length	42"	1067 mm	44"	1118 mm	50"	1270 mm
Width	22"	559 mm	28"	711 mm	28"	711 mm
Height	42"	1067 mm	42"	1067 mm	42"	1067 mm

Changes to specifications may occur without notice.

## Tube and Pipe Notcher Capacities

	TN-800		TN-900	
	Imperial	Metric	Imperial	Metric
Mild Steel Pipe (Schedule 40)	2.5"	74 mm (4 mm)	2.5"	74 mm (4 mm)
Aluminum Pipe (Schedule 40)	2.5"	74 mm (4 mm)	2.5"	74 mm (4 mm)
Stainless Steel Pipe (Schedule 40)	2.5"	74 mm (3.7 mm)	2.5"	74 mm (3.7 mm)
Mild Steel Round Tube (Wall)	3"	76 mm (3 mm)	3"	76 mm (3 mm)
Aluminum Round Tube (Wall)	3"	76 mm (4 mm)	3"	76 mm (4 mm)
Stainless Steel Round Tube (Wall)	3"	76 mm (3 mm)	3"	76 mm (3 mm)
Chromolly Round Tube (Wall)	3"	76 mm (3 mm)	3"	76 mm (3 mm)
Mild Steel Solid Rod	3"	76 mm	3"	76 mm
Mild Steel Square Tube	3"	76 mm (3 mm)	3"	76 mm (3 mm)
Minimum Outside Diameter (OD)	0.5"	13 mm	0.75"	19 mm
Power Requirements	220V, single-phase, 50Hz		220V, single-phase, 50Hz	
Weight	610 Lbs.	277 kg	475 Lbs.	216 kg
Length	44"	1118 mm	68"	1727 mm
Width	28"	711 mm	40"	1016 mm
Height	42"	1067 mm	43"	1092 mm

Changes to specifications may occur without notice.